

## Introduction

Rayzer's Polarization Maintaining Fused Tap Coupler (PMTC) series product, is used to divide input polarization maintaining fiber into two outputs according to the established spectral ratio. It is widely used in the fields of fiber laser, fiber amplifier, fiber communication and fiber sensing, with compact configuration, low insertion loss, low polarization related loss and high stability.



## Specification

Parameter	Unit	Values							
Configuration	-	1X2 or 2X2							
Center Wavelength	nm	1064							
Operating Wavelength Range	nm	±15							
Max.PDL	dB	0.1							
Typ. Excess Loss	dB	0.4							
Max. Excess Loss	dB	0.6							
Typ. Extinction Ratio	dB	20							
Min.Extinction Ratio	dB	18							
Min. Return Loss	dB	50							
Handing Power	mW	500							
Max. Tensile Load	N	5							
Fiber Type	-	PM980							
Working Temperature	°C	-5 to +75°C							
Storage Temperature	°C	-40 to +85°C							
Coupling Ratio and Tolerance									
Coupling Ratio	%	1/99	2/98	5/95	10/90	20/80	30/70	40/60	50/50
Tolerance	%	±0.3	±0.5	±0.7	±1.0	±2.0	±2.0	±2.5	±3.0

\*IL is 0.3 dB higher, RL is 5 dB lower, and ER is 2 dB lower for each connector added. Connector key is aligned to slow axis.

\*Above specifications are for device without connector and may change without notice.

## Ordering Information

### PMTC-①-②-③-④-⑤-⑥-⑦-⑧

① Center Wavelength	② Configuration	③ Coupling Ratio	④ Fiber Type	⑤ Fiber Length	⑥ Fiber Jacket	⑦ Connector Type	⑧ Working Axis
1064-1064nm	1×2-1×2	1/99-1/99	PM980	1-1M	0-Bare Fiber	FU-FC/PC	F-Fast Axis Blocked
1550-1550nm	2×2-2×2	10/90-10/90	PM1550	S-Specify	1-900μm Loose Tube	FA-FC/APC	B-Both Axis Blocked
2000-2000nm		50/50-50/50	S-Specify		2-2mm Cable	S-specify	S-specify
S-Specify		S-Specify					